

NIT 64/DISKSM Dated 02-12-2024

Photocopy Machine : Specification

GENERAL

Functions	Print, Scan, Copy
Operation panel	4-Line LCD
Warm-up time	19 seconds
First output speed: B/W	6.5 seconds
Continuous output speed	27 ppm
Memory: Standard/Max.	512 MB
ARDF capacity:	50 sheets (only for M 2701)
Weight	M2700 : 34 kg M2701 : 39 kg
Dimensions: W x D x H	M2700 : 587 x 581 x 560 mm M2701 : 587 x 581 x 639 mm
Power source	220 - 240 V, 50/60 Hz
Laser classification	Class 1 Laser Product (IEC60825 - 1:2014)

COPIER

Multiple copying	Up to 999 copies
Resolution	600 x 600 dpi
Zoom	From 25% to 400% in 1% steps

PRINTER

CPU	Q5310 400 MHz
Printer language	Standard (GDI)
Print resolution	600 x 600 dpi
Network interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T USB2.0 Type B
Network interface: option	Wireless LAN (IEEE 802.11 a/b/g/n/ac)
Mobile printing capability	Apple AirPrint™, Mopria
Windows® environments	Windows® 7, Windows® 8.1, Windows® 10, Windows® Server 2008, Windows® Server 2012, Windows® Server 2016

SCANNER

Scanning: B/W	18 ipm
Scanning: full colour	6 ipm
Resolution: maximum	600 dpi
Bundled drivers	Network TWAIN
File formats	Single Page TIFF, Multi Page TIFF, Single Page JPEG, Single Page PDF, Multi Page PDF
Scan modes	Email, Folder, USB

PAPER HANDLING

Recommended paper size	A3, A4, A5, A6, B4, B5
Paper input: standard	500 sheets tray + 100 sheet bypass
Paper input: maximum	1,600 sheets
Paper output: standard	250 sheets
Paper weight	Trays: 52 - 105 g/m ² Bypass: 52 - 216 g/m ²

ECOLOGY

Power consumption:	Maximum: Less Than 1,550W Ready mode: 94W Sleep mode: 0.97W
TEC value	Less than 1.3 kWh

SECURITY

Features	Locked Print, IPsec communication, Transport Layer Security (TLS), SMTP over SSL, Wireless LAN encryption, User codes
----------	---

INPUT TRAY OPTIONS

1x 500-sheet paper tray, 2x 500-sheet paper tray